


EHK381V




Pitch:3.81mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	130V
Rated current	10A	8A
Wire range	1.5mm ²	
Solid wire(AWG)	28~16	
Stranded wire(AWG)	28~16	
Rated surge voltage (UL/IEC/Max.)	1.6 / 1.25 / KV	
Torque(Lb-in)	1.7	
Screw	M2	
Wire strip length		
Pole	Cat. No.	
02	EHK381V-02P	
:	:	
:	:	
16	EHK381V-16P	




EHK500V(EHK508V)




Pitch:5.00mm(5.08mm)

Approval		
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2 / 4 KV	
Torque(Lb-in)	4	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
02	EHK500V-02P(EHK508V-02P)	
03	EHK500V-03P(EHK508V-03P)	



EEHK508V




Pitch:5.08mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2 / 4 KV	
Torque(Lb-in)	4	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
2X2	EEHK508V-04P	
3X2	EEHK508V-06P	



EHK508V2L




Pitch:5.08mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2 / 4 KV	
Torque(Lb-in)	4	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
2X2	EHK508V2L-04P	
3X2	EHK508V2L-06P	



EHK508V3L




Pitch:5.08mm

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2 / 4 KV	
Torque(Lb-in)	4	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
2X3	EHK508V3L-06P	
3X3	EHK508V3L-09P	




EHK500R(EHK508R)




Pitch:5.00mm(5.08mm)

Approval		
Technical Data	UL	IEC
Rated voltage	300V	250V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2 / 4 KV	
Torque(Lb-in)	4	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
02	EHK500R-02P(EHK508R-02P)	
03	EHK500R-03P(EHK508R-03P)	



EHK750V(EHK762V)



Pitch:7.50mm(7.62mm)

Approval		
Technical Data	UL	IEC
Rated voltage	300V	750V
Rated current	25A	24A
Wire range	2.5mm ²	
Solid wire(AWG)	24~12	
Stranded wire(AWG)	24~12	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / KV	
Torque(Lb-in)	3.5	
Screw	M2.5	
Wire strip length	6~7mm	
Pole	Cat. No.	
02	EHK750V-02P(EHK762V-02P)	
03	EHK750V-03P(EHK762V-03P)	